



WELL TYPE: APPRAISAL	FLUID WT:	MAX DOGLEG: 3.1 @
FIRST COMPLETED:	RTE: 85	MAX DEVIATION: 43' @
WORKOVER DATE:	SWAB:	MINIMUM ID: 8.5" @
WORKOVER NO.:	KOP: 3460	AV PAY ANGLE:
ANNULUS FLUID:	HUD:	REF LOG:

CASING / LINER / TUBING DATA							
SIZE	WEIGHT	GRADE	CONN.	JNTS	TOP MD	BTM MD	BTM TVD
30"	456	X-52	H60D/MT		541	701	701
30"	309	X-52	S60/MT		701	724	724
30"	309	X-52	BWP		724		
20"	129	X-56	H-90D		469		
20"	129	X-56	SL-BOSS			1600	1600
13 3/8"	68	L-80	DINO VAM		469	3350	3212
10-3/4"	60.7	L-80	VAM TOP		469	4872	3855
9-5/8"	53	L-80	VAM TOP		4872	5272	3898

WELLHEAD DATA			
DESCRIPTION	MAKER	TYPE	SIZE & PRESSURE
XMAS TREE WELLHEAD TUBING SPOOL TUBING HANGER	DRILL-QUIP	SS10	18 3/4" BORE 10k

MD (ft)	TVD (ft)	DIAGRAM	DESCRIPTION	ID (in)	OD (in)	DRIFT (in)	LENGTH (ft)	DEV (deg)	COMMENTS
469	469		SEABED 30" + 20" + 13-3/8" CUT 10FT BELOW SEABED Environmental Cement Plug						Note: All depths refer to top of component and DFE unless otherwise stated.
724	724		30" CONDUCTOR SHOE					0'	
734	734		36" RAT HOLE (H-O 18' BEHIND BIT)						
746	746		26" RAT HOLE						
1540	1540		CASING SHOE 20" SL-BOSS 133 LB/FT L-80 CASING PRESSURE TESTED TO 1160PSI					0'	
1565	1565		26" RAT HOLE						
1700	1700		TTOC 13-3/8"						
2950			CEMENT PLUG #2 TOC						
3368	3226		CASING SHOE 13-3/8" DINO VAM 68 LB/FT L-80 . FIT AT 13-3/8" SHOE 13.0 ppg					41'	
3380	3238		RAT HOLE 17-1/2"						
3450	3303	10-3/4" CASING CUT DEPTH. HI VIS PILL							
4272	3704	TTOC 10-3/4" x 9-5/8"							
4300	3714	TOC PLUG #1 TAGGED + TESTED TO 500psi ABOVE LOCAL FRACTURE							
4800	3841	MECHANICAL BRIDGE PLUG TAGGED HALLIBURTON EZ- SV							
4872	3855	CASING CROSS-OVER 10-3/4" x 9-5/8"							
5000		GRAVEL PACK PACKER SC-2R							
5100		MAIN HEIMDAL UNIT III							
		TUBING							
		LINER SETTING SLEEVE 7-5/8"							
5272	3898	CASING SHOE 9-5/8" VAM TOP 53.5 LB/FT							
5280	3898	GRAVEL PACK SCREENS 4-1/2"							
		PRE-PACKED SCREEN							
		TELLTALE SCREEN							
		BASE OF SAND SCREENS							
6750	3898	LINER SHOE 7-5/8" HYDRIL 513 29.7 LB/FT L-80							
7272	3898	TD 8-1/2" SECTION							

NOTE:
THIS SAMPLE, INCLUDING THE FORM LAYOUT AND EQUIPMENT SYMBOL BLOCKS AND THEIR IMAGES ARE COPYRIGHTED UNDER THE SAME TERMS AND CONDITIONS AS PETROFOCUS COMPLETIONS MANAGER SOFTWARE. PLEASE DO NOT REPRODUCE, COPY OR DISTRIBUTE WITHOUT THE EXPRESS CONSENT OF PETROFOCUS.

© PETROFOCUS 1998-2011